



Cordless Cooler & Warmer Box
CW003G / CW001G / DCW180



XGT
40V L⁺ION
max

18V
LITHIUM-ION

-18°C ~ 60°C [0°F ~ 140°F]

Keep cold, Keep hot



CW001G



CW003G

CW003G



Capacity
7L

CW001G



two in parallel or one



Capacity
20L

DCW180



two in parallel or one



Capacity
20L

XGT
40V^{max} Li-ion

18V
LITHIUM-ION

-18°C ~ 60°C
[**0°F ~ 140°F**]

More detailed inside temperature settings

(CW003G / CW001G only)

Cool storage

seven inside temperature settings

-18°C ~ 10°C [0°F ~ 50°F]



Hot storage

seven inside temperature settings

30°C ~ 60°C [85°F ~ 140°F]



-18°C Cold
[0°F]

-10°C Cold
[15°F]

5°C Cool
[40°F]

30°C Warm
[85°F]

Freeze the ice pack

Cool the drink

Warm the caulk tube

Caulk tubes to be warmed must be brand new and unopened. Also caulk tubes must be stored in the box within the storage temperature range recommended by the manufacturer of caulk tubes.*

*Do not store opened caulk tubes with foods because they produce volatile gas.

Compatible with 4 power sources (CW003G / CW001G)

Compatible with 3 power sources (DCW180)

1. 40V^{max} XGT battery



2. 18V LXT battery



3. AC (through AC adapter)



4. 12V/24V DC (cigar socket)



CW003G

Compatible with 4 power sources

40Vmax XGT battery / 18V LXT battery / AC / 12V/24V DC (cigar socket)
Any one of XGT/LXT batteries can be installed.



7L
(1.8gal)



Able to store six 500mL plastic bottles vertically (up to 220mm in height).



U-shaped carry handle

By attaching optional Shoulder belt, you can also hang this box on your shoulder.



Compact design

- Compact size of this box can be placed on the seats or foot space in passenger seat of cars.
- Convenient size for one to several people.

Work amount on full battery charge

with BL4040 batteries

-18°C [0°F] about 5.5 h	5°C [40°F] about 13.5 h	60°C [140°F] about 5.5 h
--------------------------------------	--------------------------------------	---------------------------------------

IPX4-rated water resistance



USB output port



Bottle opener



Indication lamps



CW001G


Compatible with 4 power sources

40Vmax XGT battery* (two in parallel or one) / 18V LXT battery* (two in parallel or one) / AC / 12V/24V DC (cigar socket)

*Also can be powered by the combination of one XGT battery and one LXT battery.



20L
(5.3gal)



Able to store up to four 2L plastic bottles or twenty 500mL plastic bottles.

- IPX4-rated water resistance
- USB output port
- Bottle opener
- Indication lamps
- Large 100mm casters

Work amount on full battery charge

with two BL4040 batteries

-18°C [0°F] about 8 h	5°C [40°F] about 22.5 h	60°C [140°F] about 7 h
------------------------------------	--------------------------------------	-------------------------------------

Grips for carrying by hands



Carrying handle



DCW180

Compatible with 3 power sources

18V LXT battery (two in parallel or one) / AC / 12V/24V DC (cigar socket)



20L
(5.3gal)



Able to store up to four 2L plastic bottles or twenty 500mL plastic bottles.

- IPX4-rated water resistance
- USB output port
- Bottle opener
- Large 100mm casters

Work amount on full battery charge

with two BL1860B batteries

-18°C [0°F] about 5 h	5°C [40°F] about 17 h	60°C [140°F] about 4 h
------------------------------------	------------------------------------	-------------------------------------

Grips for carrying by hands



Carrying handle



photo: CW001G

Comfort/Lifestyle

Cordless Radio with Lantern

MR009G

40V max



DMR056 / DMR055

18V



Job Site Radio

MR001G / MR002G

40V max

18V

12V max



MR003G / MR004G

40V max

18V

12V max



MR006G / MR007G

40V max

18V

12V max



LED Flashlight

ML001G

40V max



Cordless LED Worklight

ML002G

40V max



Cordless Flashlight

ML006G

40V max



ML007G

40V max



Cordless Fan

CF001G

40V max



Cordless Kettle

KT001G

40V max



DKT360

18V x2



Cordless Coffee Maker

DCM501

18V

12V max



Accessories

AC adapter



Charging Time

CW003G / CW001G

	DC40RA	DC40RC		Fast Charging		
				DC18RC	DC18RD	DC18SD
BL1815N 1.5Ah	22 min	30 min	BL1815N 1.5Ah	15 min	30 min	
BL4020 2.0Ah	22 min	30 min	BL1820B 2.0Ah	24 min	45 min	
BL4025 2.5Ah	28 min	38 min	BL1830B 3.0Ah	22 min	60 min	
BL4040 4.0Ah	45 min	67 min	BL1840B 4.0Ah	36 min	90 min	
BL4050F 5.0Ah	50 min	85 min	BL1850B 5.0Ah	45 min	110 min	
BL4080F 8.0Ah	76 min	170 min	BL1860B 6.0Ah	55 min	130 min	

Cordless Cooler & Warmer Box

CW003G / CW001G / DCW180

	CW003G	CW001G	DCW180
Capacity	7 L (1.8 gal)	20 L (5.3 gal)	20 L (5.3 gal)
Cooling system	Compressor	Compressor	Compressor
Cooling Capacity	-18 / -15 / -10 / -5 / 0 / 5 / 10°C (0 / 5 / 15 / 25 / 30 / 40 / 50°F)	-18 / -15 / -10 / -5 / 0 / 5 / 10°C (0 / 5 / 15 / 25 / 30 / 40 / 50°F)	-18 / -10 / 0 / 5 / 10°C (0 / 15 / 30 / 40 / 50°F)
Warming system	Heater	Heater	Heater
Warming Capacity	30 / 35 / 40 / 45 / 50 / 55 / 60°C (85 / 95 / 105 / 115 / 120 / 130 / 140°F)	30 / 35 / 40 / 45 / 50 / 55 / 60°C (85 / 95 / 105 / 115 / 120 / 130 / 140°F)	55 / 60°C (130 / 140°F)
Run Time (hrs)	w/BLBL4040, -18 / 5 / 60°C: 5.5 / 13.5 / 5.5	w/BLBL4040 X2, -18 / 5 / 60°C: 8 / 22.5 / 7	w/BL1860B X2, -18 / 5 / 60°C: 5 / 17 / 4
Cord Length	AC Adapter / Cigar Socket Cable: 2 / 2.5 m (6.5 / 8.2 ft)	AC Adapter / Cigar Socket Cable: 2 / 2.5 m (6.5 / 8.2 ft)	AC Adapter / Cigar Socket Cable: 2 / 2.5 m (6.5 / 8.2 ft)
Dimensions (L x W x H)	456 x 245 x 308 mm (18 x 9-5/8 x 12-1/8")	663 x 341 x 372 mm (26-1/8 x 13-3/8 x 14-5/8")	623 x 341 x 371.5 mm (24-1/2 x 13-3/8 x 14-5/8")
Net weight	7.9 - 9.4 kg (17.4 - 20.7 lbs.)	13.8 - 17.3 kg (30.4 - 38.1 lbs.)	13.3 - 14.3 kg (29.3 - 32.0 lbs.)

Standard Equipment : Shoulder Belt, AC Adaptor, Cigar Socket Cable

Not covered by EPTA-Procedure

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202205