

Kettenmodell Chain Type	290	092	480	093	099	696	484	086	686	466
Rückschlagreduzierende Eigenschaften Kickback reducing features										
Kettenteilung Pitch	 3/8" (9,5mm)	 3/8" (9,5mm)	 3/8" (9,5mm)	 3/8" (9,5mm)	 3/8" (9,5mm)	 3/8" (9,5mm)	 .325" (8,2mm)	 .325" (8,2mm)	 .325" (8,2mm)	 1/4" (6,3mm)
Schienennutbreite Gauge	 .043" (1,1mm)	 .050" (1,3mm)	 .050" (1,3mm)	 .058" (1,5mm)	 .058" (1,5mm)	 .058" (1,5mm)	 .050" (1,3mm)	 .058" (1,5mm)	 .058" (1,5mm)	 .050" (1,3mm)
Zahnform Cutter design	 semi chisel Halbmeißel	 semi chisel Halbmeißel	 semi chisel Halbmeißel	 semi chisel Halbmeißel	 full chisel Vollmeißel	 full chisel Vollmeißel	 semi chisel Halbmeißel	 semi chisel Halbmeißel	 full chisel Vollmeißel	 semi chisel Halbmeißel
Schärfwinkel Top plate filing angle	 30°	 30°	 30°	 35°	 25°	 25°	 30°	 30°	 25°	 30°
Feilhaltwinkel File guide angle	 90°	 90°	 90°	 90°	 10°	 10°	 10°	 10°	 10°	 10°
Dachschneidewinkel Top-Plate cutting angle	 50°	 60°	 60°	 60°	 60°	 60°	 60°	 60°	 60°	 60°
Brustwinkel Side-Plate angle	 80°	 80°	 80°	 85°	 60°	 60°	 85°	 85°	 60°	 85°
Tiefenbegrenzerabstand Depth gauge setting	 .025" 0,64mm	 .025" 0,64mm	 .025" 0,64mm	 .025" 0,64mm	 .025" 0,64mm	 .025" 0,64mm	 .025" 0,64mm	 .025" 0,64mm	 .025" 0,64mm	 .025" 0,64mm
Rundfeile / Round File (Erste Hälfte / At first half)	 11/64" 4,5mm	 5/32" 4,0mm	 5/32" 4,0mm	 7/32" 5,5mm	 7/32" 5,5mm	 7/32" 5,5mm	 3/16" 4,8mm	 3/16" 4,8mm	 3/16" 4,8mm	 5/32" 4,0mm
Rundfeile / Round file (Zweite Hälfte/ Later on)	-	-	-	 3/16" 4,8mm	 3/16" 4,8mm	 3/16" 4,8mm	 11/64" 4,5mm	 11/64" 4,5mm	 11/64" 4,5mm	 5/32" 4,0mm