



# Cordless Framing Nailer DBN900 / DBN901



Capable of driving nails up to 90mm /  
Similar feel to using pneumatic nailer

## DBN900

Clipped-head



Nail capacity

Length  
**50-90 mm**

Gauge  
**2.9-3.3 mm**

Collation angle display  
**30-34 °**



## DBN901

Round-head



Nail capacity

Length  
**50-90 mm**

Gauge  
**2.9-3.8 mm**

Collation angle display  
**21 °**



Powered by 18V LXT Li-Ion battery



photo: DBN900

**LED job light**

- Single LED
- With preglow and afterglow functions




**Driving depth adjustment**

Adjustable with the dial



**Window for checking remaining nail quantity**



**Anti-dry fire mechanism**

The anti-dry fire mechanism is activated before the number of remaining nails reaches zero, avoiding missed shots.

**Anti-slip nose**

Tip shape that resists slipping when driving nails at an angle



**Operation mode**

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)

**Hooks**

- Different hooks can be attached to the left and right sides for various work applications.
- The rafter hook can be attached to the opposite side of the belt hook. The width of the hook portion is 2-1/2", allowing for hooking on ladders, scaffolding, and 3x timbers.

**Accessories**

**Extended capacity magazine set**

Model: DBN900  
Part No. 1914P1-6  
Maximum magazine capacity: 97 nails



Model: DBN901  
Part No. 1914P9-0  
Maximum magazine capacity: 78 nails



**Charging Time**

		Fast Charging	
		DC18RC	DC18SD
<b>BL1815N</b> 1.5Ah	<b>15 min</b>	<b>30 min</b>	
<b>BL1820B</b> 2.0Ah	<b>24 min</b>	<b>45 min</b>	
<b>BL1830B</b> 3.0Ah	<b>22 min</b>	<b>60 min</b>	
<b>BL1840B</b> 4.0Ah	<b>36 min</b>	<b>90 min</b>	
<b>BL1850B</b> 5.0Ah	<b>45 min</b>	<b>110 min</b>	
<b>BL1860B</b> 6.0Ah	<b>55 min</b>	<b>130 min</b>	

**Cordless Framing Nailer**

**DBN900 / DBN901**

	<b>DBN900</b>	<b>DBN901</b>
Auto Firing Stop		
Built-in Job Light		
Anti-restart function		
Depth Adjustment		
Sequential and Bump-fire		
Carrying Case		
<b>Standard Equipment :</b>		
Hex wrench, Rafter hook, Nose adapter, Battery, Charger		
<b>Capacity</b>	Length: 50 - 90 mm (2 - 3-1/2 ") Gauge: 2.9 - 3.3 mm (0.113 - 0.131 ") Collation angle display: 30 - 34 °	Length: 50 - 90 mm (2 - 3-1/2 ") Gauge: 2.9 - 3.8 mm (0.113 - 0.148 ") Collation angle display: 21 °
<b>Magazine capacity</b>	51 - 58 nails	36 - 41 nails
<b>Work volume on a full battery charge</b>	w/ BL1860B: 1,000	w/ BL1860B: 1,000
<b>Rapid firing capability shots per second</b>	2	2
<b>Vibration level</b>	EN60745-2-16:3.4 m/s <sup>2</sup>	EN60745-2-16:3.5 m/s <sup>2</sup>
<b>Vibration K Factor</b>	EN60745-2-16:1.5 m/s <sup>2</sup>	EN60745-2-16:1.5 m/s <sup>2</sup>
<b>Sound pressure level</b>	EN60745-2-16: 90 dB (A)	EN60745-2-16: 92 dB (A)
<b>Noise K factor</b>	EN60745-2-16: 3 dB (A)	EN60745-2-16: 3 dB (A)
<b>Sound power level</b>	EN60745-2-16: 101 dB (A)	EN60745-2-16: 103 dB (A)
<b>Dimensions (L x W x H)</b>	w/ BL1860B: 326 x 186 x 358 mm (12-7/8 x 7-3/8 x 14-1/8")	w/ BL1860B: 389 x 189 x 358 mm (15-3/8 x 7-1/2 x 14-1/8")
<b>Net weight</b>	w/ BL1820B - BL1860B: 4.9 - 5.4 kg (10.8 - 11.9 lbs.)	w/ BL1820B - BL1860B: 5.0 - 5.4 kg (11.0 - 11.9 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



PRINTED IN JAPAN 202410

www.makita.com