



# Cordless Impact Driver TD112D



## 135 N·m of Max Torque from a compact body



**Rubberized bit sleeve**  
protects workpiece from scratches and damage.

**Minimized bit wobbling**  
Bit wobbling is minimized by using two ball bearings as a new anvil holder.

**Single LED job light**  
with preglow and afterglow functions

**Variable speed control switch**  
with a trigger having a short pull length to reach full speed

**Impact power selection**

Max fastening torque:  
**135 N·m** **80 N·m**  
Hard impact mode    Soft impact mode

### Auto-stop system

Indication lamp warn assembly worker visually and audibly of battery power reduction. If battery power reduces further, the motor automatically stops to prevent incomplete fastening.



### Accessories

#### Protector

Part No. 422718-7



#### Hook

Part No. 281012-4



### Cordless Impact Driver TD112D

|                    |                                 |   |
|--------------------|---------------------------------|---|
| Variable Speed     | <b>Capacity</b>                 | High Strength Bolt: M5 - M12 (3/16 - 1/2")<br>Standard Bolt: M5 - M14 (3/16 - 9/16")  |
| Brake              | <b>Hex Shank</b>                | 6.35 mm (1/4")  |
| Reversing          | <b>Center Height</b>            | 25 mm   |
| Electronic 2-Speed | <b>Impacts Per Minute (IPM)</b> | Hard / Soft: 0 - 3,900 / 0 - 3,300  |
| Built-in Job Light | <b>No Load Speed (RPM)</b>      | Hard / Soft: 0 - 3,000 / 0 - 2,000  |
|                    | <b>Max Fastening Torque</b>     | Hard / Soft: 135 / 80 N·m (1,200 / 700 in.lbs.)   |
|                    | <b>Sound Power Level</b>        | 104 dB(A)   |
|                    | <b>Sound Pressure Level</b>     | 93 dB(A)  |
|                    | <b>Vibration Level*</b>         | 10.9 m/s <sup>2</sup>   |
|                    | <b>Dimensions (L x W x H)</b>   | w/ BL1016/BL1021B: 145 x 64 x 221 mm (5-3/4 x 2-1/2 x 8-3/4")<br>w/ BL1041B: 145 x 64 x 240 mm (5-3/4 x 2-1/2 x 9-1/2")<br>w/o Battery: 145 x 52 x 195 mm (5-3/4 x 2-1/16 x 7-5/8") |
|                    | <b>Net weight</b>               | 0.99 - 1.2 kg (2.2 - 2.6 lbs.)  |

\*Impact tightening of fasteners of the maximum capacity of the tool

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202108